

# SAFETY DATA SHEET

FILE NO.: Incoming\_SDS\_HFC-125\_00  
SDS DATE: January 2014

## SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** HFC-125  
**SYNONYMS:** Pentafluoroethane; R-125  
**Product Use:** Fire extinguishing agent, refrigerant

**SHIPPER NAME AND ADDRESS:**

**HEALTH EMERGENCY PHONE:** 1-800-222-1222 (Poison Control Center)  
**TRANSPORTATION EMERGENCY PHONE:** 1-800-424-8802 (National Response Center)  
**GENERAL INFORMATION:** 1-800-467-4922 (U.S. Department of Transportation Pipeline and Hazardous Materials Safety Administration Hazardous Materials Information Center – M-F, 9am-5pm)

**SDS PREPARED BY:** A-Gas RemTec

## SECTION 2: HAZARD IDENTIFICATION

**HAZARD CLASSIFICATION:** Gas under pressure, Liquefied gas  
Skin irritation, Category 3  
Eye irritation, Category 1

**SIGNAL WORD:** **WARNING**

**HAZARD STATEMENT:** Liquid and gas under pressure.  
Overheating and overpressurizing may cause gas release or violent cylinder bursting.  
Simple asphyxiant.



**PRECAUTIONARY STATEMENTS:** Keep container tightly closed in a cool/well-ventilated place.  
Keep away from heat/sparks/open flame. – No smoking.  
Do not allow liquid or vapors to come into contact with skin or eyes.  
Wear protective gloves and eye/face protection.  
Do not breathe mist/vapors.  
Use only in a well-ventilated area.  
Avoid release to the environment.

**OTHER HAZARDS:** May decompose on contact with flames or extremely hot metal surfaces to produce toxic and corrosive products.  
Vapor reduces oxygen available for breathing and is heavier than air.  
Harmful if inhaled and may cause heart irregularities, unconsciousness, or death.  
Liquid contact with eyes or skin may cause frostbite

**ASHRAE STANDARD 34 SAFETY RATING:** A1

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

<u>INGREDIENT NAME</u>	<u>FORMULA</u>	<u>CAS NUMBER</u>	<u>WEIGHT %</u>
Pentafluoroethane	C <sub>2</sub> HF <sub>5</sub>	354-33-6	100

Trace impurities and additional material names not listed above may also appear in Section 15 toward the end of this SDS. These materials may be listed for local "Right-To-Know" compliance and for other reasons.

## SECTION 4: FIRST AID MEASURES

**SKIN:** Flush exposed skin with lukewarm water (not hot), or use other means to warm skin slowly. Get medical attention if frostbitten by liquid or if irritation persists.

# SAFETY DATA SHEET

FILE NO.: Incoming\_SDS\_HFC-125\_00

SDS DATE: January 2014

**EYES:** Immediately flush with large amounts of water for at least 15 minutes. Get medical attention if irritation persists.

**INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

**INGESTION:** Not applicable - product is a gas at ambient temperatures.

**ADVICE TO PHYSICIAN:** Because of the possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used with special caution and only in situations of emergency life support. Treatment of overexposure should be directed at the control of symptoms and the clinical conditions.

---

## SECTION 5: FIRE-FIGHTING MEASURES

---

**EXTINGUISHING MEDIA:** This product is a fire extinguishing media. Use extinguishing media appropriate to surrounding fire conditions.

**UNUSUAL FIRE AND EXPOSION HAZARDS:** Product is not flammable at ambient temperatures and atmospheric pressure. However, this material will become combustible when mixed with air under pressure and exposed to strong ignition sources.  
May decompose on contact with flames or extremely hot metal surfaces to produce toxic and corrosive products.  
Cylinders are equipped with pressure release devices to vent contents exposed to high temperatures.  
Container may explode if heated due to resulting pressure rise.

**SPECIAL FIRE-FIGHTING PRECAUTIONS/INSTRUCTIONS:** Firefighters should wear self-contained, NIOSH-approved breathing apparatus for protection against possible toxic decomposition products. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed containers cool.

---

## SECTION 6: ACCIDENTAL RELEASE MEASURES

---

**ACCIDENTAL RELEASE MEASURES:** If the release is caused by an open valve and it is safe for operator to close, do so. If possible to transfer the remaining gas in the cylinder in a safe manner to a separate tank, do so. If the release cannot be isolated or closed and it is a significant amount, allow the gas to release in place or safely move cylinder to a safe area. Evacuate area in the event of a significant release in an enclosed area. Keep upwind. Ventilate area, especially low places. Remove open flames and heating elements. Disperse gas with floor level forced air.

**Spills and releases may have to be reported to Federal and/or local authorities. See Section 15 regarding reporting requirements.**

---

## SECTION 7: HANDLING AND STORAGE

---

**HANDLING AND STORAGE:** Avoid breathing gas. Avoid contact with eyes, skin and clothing. Keep container closed. Use only with adequate ventilation. Use properly rated DOT or ASME cylinders/tanks only. Follow standard safety precautions for handling and use of compressed gas cylinders. Store in a cool, well-ventilated area of low fire risk and out of direct sunlight. Protect cylinder and its fittings from physical damage. Storage in subsurface locations should be avoided. Close valve tightly after use and when empty.

**OTHER PRECAUTIONS:** Do not mix with oxygen or air above atmospheric pressure.

---

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

---

### EXPOSURE LIMITS:

<u>INGREDIENT NAME</u>	<u>CAS NUMBER</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>OTHER LIMIT(S)</u>
Pentafluoroethane	354-33-6	None	None	*1000ppm (TWA) **1000ppm (TWA)

\* = Workplace Environmental Exposure Level (AIHA)

\*\* = Occupational Exposure Level (ASHRAE)

### OTHER EXPOSURE LIMITS FOR POTENTIAL DECOMPOSITION PRODUCTS:

Hydrogen Fluoride: ACGIH TLV = 3 ppm ceiling

**ENGINEERING CONTROLS:** Provide local ventilation at filling zones and areas where leakage is probable. Mechanical (general) ventilation may be adequate for other operating and storage areas.

**PERSONAL PROTECTIVE EQUIPMENT:**

# SAFETY DATA SHEET

FILE NO.: Incoming\_SDS\_HFC-125\_00

SDS DATE: January 2014

**SKIN:** Wear appropriate chemical resistant protective clothing and chemical resistant gloves to prevent skin contact. Consult glove manufacturer to determine appropriate type of glove material for given application. Wash contaminated clothing and clean protective equipment before reuse. Wash skin thoroughly after handling.

**EYES:** Where there is reasonable probability of liquid contact, wear chemical safety goggles, and have eye flushing equipment available.

**RESPIRATORY:** None generally required for adequately ventilated work situations. For accidental release or non-ventilated situations, use a self-contained, NIOSH-approved breathing apparatus or supplied air respirator. For escape, use the former or a NIOSH-approved gas mask with organic vapor canister.

**ADDITIONAL RECOMMENDATIONS:** Wash hands after use and before eating or drinking.

---

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

---

**APPEARANCE:** Clear, colorless gas  
**PHYSICAL STATE:** Gas at ambient temperatures  
**MOLECULAR WEIGHT:** 120.02 g/mol  
**CHEMICAL FORMULA:** C<sub>2</sub>HF<sub>5</sub>  
**ODOR:** Faint ethereal odor  
**ODOR THRESHOLD:** Not available  
**RELATIVE DENSITY:** Not available  
**VISCOSITY:** Not available  
**SPECIFIC GRAVITY (water = 1.0):** 1.21  
**SOLUBILITY IN WATER:** 39 mg/L @ 25°C  
**pH:** Neutral  
**BOILING POINT:** -48.5° C  
**MELTING POINT:** -103° C  
**VAPOR PRESSURE:** 180 psia @ 21.1° C  
**VAPOR DENSITY (air = 1.0):** 4.2  
**LIQUID DENSITY:** 1.53 g/ml @ -48.5°C  
**EVAPORATION RATE (CC14 = 1.0):** > 1  
**% VOLATILES:** 100%  
**FLASH POINT:** Not applicable  
**FLASH POINT METHOD:** Not applicable  
**AUTOIGNITION TEMPERATURE:** Not available  
**DECOMPOSITION TEMPERATURE:** Not available  
**UPPER FLAMMABLE LIMIT (volume % in air):** None\*  
**LOWER FLAMMABLE LIMIT (volume % in air):** None\*  
**FLAME PROPAGATION RATE (solids):** Not applicable  
**OSHA FLAMMABILITY CLASS:** Not applicable  
**PARTITION COEFFICIENT (n-octanol/water):** 2.30 log Kow

\* Based on ASHRAE Standard 34 with match ignition.

---

## SECTION 10: STABILITY AND REACTIVITY

---

**REACTIVITY:** May cause strong exothermic reaction when exposed to freshly abraded aluminum surfaces at very high temperatures or high pressure. Chemically active metals: potassium, calcium, powdered aluminum, magnesium and zinc.

**STABILITY:** This material is chemically stable under specified conditions for storage, shipment and/or use. See Section 7 Handling and Storage for specified conditions.

**CONDITIONS TO AVOID:** Avoid contact with strong alkali or alkaline earth metals, finely powdered metals such as aluminum, magnesium or zinc and strong oxidizers, since they may react or accelerate decomposition.  
Do not mix with oxygen or air above atmospheric pressure.  
Any source of high temperature, such as lighted cigarettes, flames, hot spots or welding may yield toxic and/or corrosive decomposition products.

**HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:** Thermal decomposition products include hydrogen fluoride, hydrofluoric acid, carbon dioxide, carbon monoxide, and carbonyl fluorides.

---

## SECTION 11: TOXICOLOGICAL INFORMATION

---

**ROUTES OF EXPOSURE:** Inhalation, Skin contact, Eye contact

**ACUTE EFFECTS OF EXPOSURE:** Frostbite from skin contact with liquid.

# SAFETY DATA SHEET

FILE NO.: Incoming\_SDS\_HFC-125\_00

SDS DATE: January 2014

High vapor concentrations are irritating to the eyes and respiratory tract and may result in central nervous system effects such as headache, dizziness, drowsiness and, in severe exposure, loss of consciousness and death.

The dense vapor of this material may reduce the available oxygen for breathing, and prolonged exposure to an oxygen-deficient atmosphere may be fatal.

Inhalation may cause an increase in the sensitivity of the heart to adrenaline, which could result in irregular or rapid heartbeats.

Medical conditions aggravated by exposure include heart disease or compromised heart function.

**CHRONIC EFFECTS OF EXPOSURE:** None known.

**ACUTE TOXICITY:** LC<sub>50</sub> (rat – 4 hr.) = 2,910 g/m<sup>3</sup>

**CHRONIC TOXICITY:** Teratogenic NOEL (rat and rabbit) = 50,000 ppm  
Subchronic inhalation (rat) NOEL ≥ 50,000 ppm  
Chronic NOEL = 10,000 ppm

**DESCRIPTION OF SYMPTOMS:** Inhalation of high concentration may lead to unconsciousness and possible death. Effects of overexposure by inhalation may include non specific discomfort, such as nausea, headache, or weakness, or temporary central nervous system depression with effects such as dizziness, headache, confusion, loss of coordination, and loss of consciousness. Higher exposures by inhalation may cause temporary alteration of the heart's electrical activity with irregular pulse, palpitations, or inadequate circulation. Individuals with pre-existing diseases of the central nervous or cardiovascular system may have increased susceptibility to the toxicity of excessive exposure.

**CARCINOGENICITY:** Not listed as a carcinogen by NTP, IARC, or OSHA

---

## SECTION 12: ECOLOGICAL INFORMATION

---

**AQUATIC TOXICITY:** No data available, but not expected to be found in aquatic environments, as product is gaseous at ambient temperatures.

**DEGRADABILITY:** The half-life for pentafluoroethane in the atmosphere is estimated to be 18 years.

**BIOACCUMULATION:** Bioaccumulation is considered unlikely for this material, due to its gaseous state at ambient temperatures and atmospheric pressure.

**ADSORPTION/LEACHING:** Adsorption/Leaching is considered unlikely for this material, due to its gaseous state at ambient temperatures and atmospheric pressure.

**OTHER ADVERSE EFFECTS:** **Ozone Depletion Potential (CFC 11 = 1.0):** 0.00  
**Global Warming Potential (CO<sub>2</sub> = 1.0):** 3,450

---

## SECTION 13: DISPOSAL CONSIDERATIONS

---

**RCRA:** Unused product is not considered to be a RCRA hazardous waste.

**DISPOSAL CONSIDERATIONS:** Recover, reclaim or recycle when practical. Dispose of in accordance with federal, state and local regulations.  
Chemical additions to, processing of, or otherwise altering this material may make this waste management information incomplete, inaccurate, or otherwise inappropriate. Furthermore, state and local waste disposal requirements may be more restrictive or otherwise different from federal laws and regulations. Contact a certified reclaimer for recovery/reclamation of this product.

---

## SECTION 14: TRANSPORT INFORMATION

---

### U.S. DEPARTMENT OF TRANSPORTATION

**UN NUMBER:** UN3220  
**UN PROPER SHIPPING NAME:** Pentafluoroethane  
**US DOT HAZARD CLASS:** 2.2, Non-Flammable Gas  
**PACKING GROUP:** Not Applicable

*OR – If charged with Nitrogen, Carbon Dioxide, or Air.....*

### U.S. DEPARTMENT OF TRANSPORTATION

**UN NUMBER:** UN1058  
**UN PROPER SHIPPING NAME:** Liquified gases, nonflammable charged with nitrogen, carbon dioxide, or air  
**US DOT HAZARD CLASS:** 2.2 Non-Flammable Gas  
**PACKING GROUP:** Not Applicable

**ENVIRONMENTAL CONCERNS:** None known.



# SAFETY DATA SHEET

FILE NO.: Incoming\_SDS\_HFC-125\_00

SDS DATE: January 2014

**BULK TRANSPORTATION:** Avoid transportation in vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the containers and what action to take in the event of an accident or an emergency.  
Prior to transporting cylinders, ensure that they are firmly secured, valves are closed and not leaking, and the valve outlet cap nuts or plugs (if provided) are correctly connected.

**SPECIAL TRANSPORTATION:** None known.

---

## SECTION 15: REGULATORY INFORMATION

---

### U.S. FEDERAL REGULATIONS

**TSCA (TOXIC SUBSTANCE CONTROL ACT):** All components of this product are listed on the TSCA Inventory list.

**CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT) and SARA (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT):**

No "Reportable Quantities" (RQs) or "Threshold Planning Quantities" (TPQs) exist for any of the ingredients in this product.

**Any spill or release resulting in the loss of any ingredient at or above its RQ requires immediate notification to the National Response Center (800-424-8802) and to your local Emergency Planning Committee.**

**SECTION 311 HAZARD CLASS:** Immediate (Acute) Health  
Sudden Release of Pressure

**SECTION 313 TOXIC CHEMICALS:** None of the ingredients in this product are classified as SARA 313 "Toxic Chemicals". CAS numbers and weight percents are found in Section 3 Composition/Information on Ingredients.

### ADDITIONAL REGULATORY INFORMATION:

**WARNING: Do not vent** to the atmosphere. **Contains Pentafluoroethane**, an HFC, a greenhouse gas which may contribute to global warming.

### FOREIGN INVENTORY STATUS:

EU-EINECS: # 2065578

---

## SECTION 16: OTHER INFORMATION

---

**PREPARED BY:** A-GasRemTec  
**DATE PREPARED:** January 2014  
**CURRENT REVISION LEVEL:** 00  
**CURRENT REVISION DATE:** 1/29/2014

**DISCLAIMER:** *This document has been provided by A-Gas RemTec to the shipper indicated on Page 1 as a courtesy, to allow the shipper to comply with applicable regulations requiring the shipment of a Safety Data Sheet for the product indicated on this document. Details given in this document are for informational purposes only, and are believed to be correct. Information is provided without warranty. A-Gas RemTec is not liable for any damage which may result from the use or reliance on this information.*